



SYM	DESCRIPTION	DATE	APPROVED	SYM	DESCRIPTION	DATE	APPROVED
-----	-------------	------	----------	-----	-------------	------	----------

**CUSTOMER DRAWING FOR REFERENCE ONLY, SAMPLES APPROVAL ARE REQUIRED!!							490
--	--	--	--	--	--	--	-----





- NOTE:
1. HOUSING MATERIAL: LCP UL94V-0, NATURAL
 2. ACTUATOR MATERIAL: LCP UL94V-0, BLACK
 3. CONTACT MATERIAL: COPPER ALLOY.
PLATING: TIN PLATING
 4. CAP MATERIAL LCP UL94V-0, WHITE.

SPECIFICATION:


1. ELECTRICAL CHARACTERISTICS:
1-1. RATING CURRENT: 1A AC/DC
1-2. VOLTAGE RATING: 50V AC/DC
2. AMBIENT TEMPERATURE RANGE: -40C~+85C

ORDER INFORMATION:
FPCe216-PtXXT-CP
FPC: FPC CONNECTOR
e: PITCH=1.00 mm
216: SERIES NO.
Pt: PCB TYPE, SURFACE MOUNT
XX: NUMBER OF CONTACTS
T: PLATING, TIN PLATING
CP: WITH CAP

NO. OF CONTACT	DIMENSIONS			
	A	B	C	D
4	3.00	5.10	9.05	11.00
5	4.00	6.10	10.05	12.00
6	5.00	7.10	11.05	13.00
7	6.00	8.10	12.05	14.00
8	7.00	9.10	13.05	15.00
9	8.00	10.10	14.05	16.00
10	9.00	11.10	15.05	17.00
11	10.00	12.10	16.05	18.00
12	11.00	13.10	17.05	19.00
13	12.00	14.10	18.05	20.00
14	13.00	15.10	19.05	21.00
15	14.00	16.10	20.05	22.00
16	15.00	17.10	21.05	23.00
17	16.00	18.10	22.05	24.00
18	17.00	19.10	23.05	25.00
19	18.00	20.10	24.05	26.00
20	19.00	21.10	25.05	27.00
21	20.00	22.10	26.05	28.00
22	21.00	23.10	27.05	29.00
23	22.00	24.10	28.05	30.00
24	23.00	25.10	29.05	31.00
25	24.00	26.10	30.05	32.00
26	25.00	27.10	31.05	33.00
27	26.00	28.10	32.05	34.00
28	27.00	29.10	33.05	35.00
29	28.00	30.10	34.05	36.00
30	29.00	31.10	35.05	37.00



RECOMMENDED PCB LAYOUT



RECOMMENDED FPC/FCC DIMENSION

TOLERANCES UNLESS OTHERWISE SPECIFIED		SIGNATURES		DATE		MODEL	
±0.20		DRAWN	AARON	23/JUL/25		FPC CONNECTOR	
SYMBOL		UNIT	SCALE	CHECKED	MELODY	23/JUL/25	
△		mm	3/1	APPROVALS			

MMT CORPORATION